



272 West Stag Park Service Road
Burgaw, NC 28425 USA
910-259-1131
1-800-403-6927 fax
www.lightguard.com

Product Bulletin



Wet-Lok Series Capacity Expanded

October 24, 2008 - LightGuard is pleased to announce that the extremely functional Wet-Lok Series is now being released with two new capacity ranges; 12 VDC, 125 watt and 12 VDC, 150 watt ratings. These new product ranges are being offered in standard location ratings as well as cold ambient, high ambient and extreme ambient listings. The expanded capacity ratings will allow for extended run times in extreme environment applications as well as the ability to support more remote head application needs. The following highlights are an example of just a few of the exceptional features available:

- ◆ Standard Smart Charger Diagnostics
- ◆ Optional self-testing diagnostics
- ◆ 8-hour run time listing on the 12V, 150 watt model in accordance with the NRC appendix R (two 18-watt lamps max)
- ◆ Third party testing and compliance to NEMA 4X and IP66 standard
- ◆ UL wet location listing standard
- ◆ NSF Class II Splash Zone listed
- ◆ All temperature ratings are at maximum rated capacity without de-rating
- ◆ Optional Smart Charger IR remote test device
- ◆ Standard wall mount capabilities with optional strapping kit for columns, poles and I-beams.

The initial Wet-Lok Series specification response has been tremendous and we believe this product enhancement will once again create another level of separation between us and our competition. As always, should you have questions or concerns regarding this matter, do not hesitate to contact us directly. Thank you for your continued support.