



a Genlyte company
272 West Stag Park Service Road
Burgaw, NC 28425 USA
Telephone: 910 259 1131
Fax: 1 800 403 6927
Website: www.lightguard.com

Product Bulletin



Wet Lok Now Standard with Self-Testing Diagnostics

June 21, 2007 - LightGuard is proud to announce that the extremely functional Wet Lok series is now being released with our Smart Charger diagnostics platform as a standard feature. Unlike the Vintage series, where the Smart Charger electronics were first employed, the Wet Lok series will be shipped from LightGuard with self-testing diagnostics as a standard feature. The following list highlights a few of the exceptional features now available:

- ◆ AC-Only or Self-Powered models
- ◆ Standard self-testing diagnostics (self-powered models)
- ◆ Two-hour emergency run time in 60°F to 90°F ambient conditions
- ◆ 10-year designed service life
- ◆ Batteries compliant with IEC 61951-1 life testing
- ◆ Red or green LED illumination in excess of 79 cd/m² average
- ◆ Single face or universal (2 faces, back plate, and canopy) configurations
- ◆ -40°F (-40°C) to 113°F (+45°C) standard operating range
- ◆ Torx® T15 tamperproof hardware with bit
- ◆ Energy Star listed
- ◆ UL wet location listed standard
- ◆ Optional Smart Charger IR remote test device

As always, should you have questions or concerns regarding this matter do not hesitate to contact us directly. Thank you for your continued support.

*Remember to keep **LightGuard** in mind for all of your emergency lighting needs!*